
## Knightsbridge



**UCLCT4** 

230V 4W LED Linkable Striplight CCT Adjustable (277mm)

www.mlaccessories.co.uk



Description230V 4W LED Linkable Striplight CCT Adjustable (277NET WEIGHT (KG)0.187FINISHWhiteDIFFUSEROpalDIMENSIONS (MM)Length - 277 Width - 22.8 Projection - 36CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP20VATTAGE (W)4.AMP TECHNOLOGYLED.AMP INCLUDEDYes.UMENS (LM)350 / 390 / 370	
FINISHWhiteDIFFUSEROpalDIMENSIONS (MM)Length - 277 Width - 22.8 Projection - 36CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP20VATTAGE (W)4AMP TECHNOLOGYLEDAMP INCLUDEDYes	mm)
DIFFUSEROpalDIMENSIONS (MM)Length - 277 Width - 22.8 Projection - 36CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP20VATTAGE (W)4AMP TECHNOLOGYLEDAMP INCLUDEDYes	
Length - 277 Width - 22.8 Projection - 36CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP20VATTAGE (W)4AMP TECHNOLOGYLEDAMP INCLUDEDYes	
DIMENSIONS (MM)Width - 22.8 Projection - 36CONSTRUCTIONConstruction - PolycarbonateCLASSIIP RATINGIP20VATTAGE (W)4AMP TECHNOLOGYLEDAMP INCLUDEDYes	
CLASSIIP RATINGIP20VATTAGE (W)4.AMP TECHNOLOGYLED.AMP INCLUDEDYes	
P RATINGIP20VATTAGE (W)4.AMP TECHNOLOGYLED.AMP INCLUDEDYes	
VATTAGE (W)4.AMP TECHNOLOGYLED.AMP INCLUDEDYes	
AMP TECHNOLOGY LED AMP INCLUDED Yes	
AMP INCLUDED Yes	
UMENS (LM) 350 / 390 / 370	
UMENS LIGHT SOURCE ONLY (LM) 395	
UMEN TOLERANCE 5%	
EFFICACY (LM/W) 106.2	
CIRCUIT WATTAGE (W) 3.9	
CT 3000/4000/6500K	
IGHT COLOUR CCT	
<b>CRI</b> >80	
SDCM <6	
RUNNING CURRENT (A) 0.031	
DISPLACEMENT FACTOR >0.7	
SVM 0.028	
PST-LM 0.008	
BEAM ANGLE (DEGREES) 140	
IFE SPAN (HRS) 30,000	-
.70B50 LIFESPAN (HRS) 54,000	



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.



## Knightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-10~40°C
INPUT VOLTAGE	230V 50Hz
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832999560

Date Created: 03/04/2023 13:22





