Xnightsbridge


DATASHEET



UCLED22WW

230V 22W LED Linkable Striplight 3000K (1438mm)

www.mlaccessories.co.uk



MLA PART CODE	UCLED22WW
DESCRIPTION	230V 22W LED Linkable Striplight 3000K (1438mm)
NET WEIGHT (KG)	0.394
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1438 Width - 22.8 Projection - 36
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	22
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	1550
LUMENS LIGHT SOURCE ONLY (LM)	2355
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	113.6
CIRCUIT WATTAGE (W)	20.7
ССТ	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.152
DISPLACEMENT FACTOR	>0.9
SVM	0.008
PST-LM	0.001
BEAM ANGLE (DEGREES)	145
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	54,000





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-10~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	2
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832977889

Date Created: 03/04/2023 13:11





