


## DATASHEET



### WP21CCT

230V IP65 IK08 21W LED Polycarbonate Wall Fitting - CCT

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



| MLA PART CODE                 | WP21CCT   |
|-------------------------------|---|
| DESCRIPTION                   | 230V IP65 IK08 21W LED Polycarbonate Wall Fitting - CCT |
| NET WEIGHT (KG)               | 0.76  |
| FINISH                        | Black   |
| DIFFUSER                      | Opal  |
| DIMENSIONS (MM)               | Height - 170<br>Width - 320<br>Projection - 136         |
| CONSTRUCTION                  | Construction - ABS<br>Construction 2 - & polycarbonate  |
| CLASS                         | II  |
| IP RATING                     | IP65  |
| IK RATING                     | IK08  |
| WATTAGE (W)                   | 21  |
| LAMP TECHNOLOGY               | SMD LED   |
| LAMP INCLUDED                 | Yes   |
| LUMENS (LM)                   | 1000/1200/1100  |
| LUMENS LIGHT SOURCE ONLY (LM) | 2250/2600/2500  |
| LUMEN TOLERANCE               | 5%  |
| EFFICACY (LM/W)               | 134.5   |
| CIRCUIT WATTAGE (W)           | 19.5  |
| CCT                           | 3000/4000/6500K   |
| LIGHT COLOUR                  | CCT   |
| CRI                           | >85   |
| SDCM                          | <6  |
| RUNNING CURRENT (A)           | 0.106   |
| DISPLACEMENT FACTOR           | >0.9  |
| SVM                           | 0.012   |
| PST-LM                        | 0.107   |
| BEAM ANGLE (DEGREES)          | 105   |

|  |   |
|--|---|
| LIFE SPAN (HRS)                          | 25,000  |
| L70B50 LIFESPAN (HRS)                    | 36,000  |
| LED COMPATIBLE                           | Yes   |
| DIMMABLE                                 | No  |
| OPERATING TEMPERATURE                    | -10~35°C  |
| INPUT VOLTAGE                            | 230V 50Hz   |
| CABLE GLAND INCLUDED                     | Blind grommet   |
| DRIVER                                   | MAX. OUTPUT - 21W<br>OUTPUT VOLTAGE - 24-42V<br>OUTPUT CURRENT - 500mA<br>ISOLATION - SELV<br>AMBIENT TEMPERATURE (Ta) - 45°C<br>CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY                                 | 3year(s)  |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598   |
| ORIGIN OF MANUFACTURE                    | China   |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes   |
| EAN                                      | 5056270854251   |

Date Created: 03/04/2023 13:56

