


DATASHEET



WW40C

230V 40W Round LED Recessed Adjustable Downlight

www.mlaccessories.co.uk



MLA PART CODE	WW40C
DESCRIPTION	230V 40W Round LED Recessed Adjustable Downlight
NET WEIGHT (KG)	1.272
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 190 Projection - 87 Recessed Depth - 122 Minimum Void - 172
CUT-OUT (MM)	Cut-out Diameter - 160
TILT (DEGREES)	40
ROTATION (DEGREES)	350
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP40 (IP20 from above)
WATTAGE (W)	40
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	4050
LUMENS LIGHT SOURCE ONLY (LM)	4050
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	102.97
CIRCUIT WATTAGE (W)	38.79
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.17
DISPLACEMENT FACTOR	>0.9
SVM	0.85

PST-LM	0.1
BEAM ANGLE (DEGREES)	30
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	54,000
DIMMABLE	No
IC RATED	No
OPERATING TEMPERATURE	35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.4
CABLE TYPE	2-core 0.75mm H03VVH2-F
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 30 - 42V OUTPUT CURRENT - 950mA POWER FACTOR - >0.9 EFFICIENCY FULL LOAD - 88.7 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 40°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832952886

Date Created: 03/04/2023 12:57

