



DATASHEET



WW40R

230V 40W Recessed LED Rectangular Wallwasher

www.mlaccessories.co.uk



MLA PART CODE	WW40R
DESCRIPTION	230V 40W Recessed LED Rectangular Wallwasher
NET WEIGHT (KG)	1.385
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Length - 240 Width - 157 Projection - 87 Recessed Depth - 85 Minimum Void - 135
CUT-OUT (MM)	Cut-out Box W/H/D - 222x125
TILT (DEGREES)	60
CONSTRUCTION	Construction - Aluminium
CLASS	II
IP RATING	IP40 (IP20 from above)
WATTAGE (W)	40
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3570
LUMENS LIGHT SOURCE ONLY (LM)	4630
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	117.46
CIRCUIT WATTAGE (W)	39.48
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.17
DISPLACEMENT FACTOR	>0.9
SVM	0.11

PST-LM	0.1
BEAM ANGLE (DEGREES)	70
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	54,000
DIMMABLE	No
IC RATED	No
OPERATING TEMPERATURE	35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.4
CABLE TYPE	2-core 0.75mm H03VVH2-F
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 55W OUTPUT VOLTAGE - 25 - 42V OUTPUT CURRENT - 950mA POWER FACTOR - >0.9 EFFICIENCY FULL LOAD - 88.2 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832954903

Date Created: 03/04/2023 12:59

