

INSTALLATION & MAINTENANCE MANUAL

HPLED1W

GENERAL INSTRUCTIONS

These instructions should be read carefully and retained after installation by the end user for future reference and maintenance.

These instructions should be used to aid installation of the following product: HPLED1W

SAFETY

- This product must be installed in accordance with the latest edition of the IEE Wiring Regulations (BS7671) and current Building Regulations. If in any doubt, consult a qualified electrician
- · Please isolate mains prior to installation or maintenance
- Check the total load on the circuit (including when this product is fitted) does not exceed the rating of the circuit cable, fuse, or circuit breaker
- · Please note the IP (Ingress Protection) rating of this product when deciding the location for installation
- This product should be installed in the upright position
- This product is safe for use as a drive-over fitting (weight load 500kg)
- . This product is Class I and must be earthed
- This product is IP65 rated

INSTALLATION

Note - If this product is being used in conjunction with an external PIR or sensor, please confirm with the manufacturer of the sensors that they are compatible with LED luminaires.

- Provide power to the required point of installation (refer to BS7671 for correct cabling methods). Suitable IP rated junction boxes should be used where required
- The power source connections should be local and accessible via a suitable IP rated enclosure
- Cut a suitable hole in the mounting surface as per the cut-out details (see Fig.1) ensuring not to infringe with any joists, gas/water pipes or electrical cables

Cut-out with sleeve	Cut-out without sleeve
60mm	40mm

Fig. 1

- Please note this product is supplied with a sleeve for direct mounting in the ground. The sleeve is not necessary for installation into decking
- We recommend not installing in areas where there is a high risk of flooding or areas where water may sit on top of the fitting (see Fig. 2)






Fig. 2

- Ensure a minimum of 300mm of drainage below the luminaire (see Fig. 2).
- There must be enough cable below the luminaire in order to carry out maintenance work (see Fig. 3)



- Connect the luminaire to the mains supply ensuring the correct polarity is observed (see Fig. 4): L - Live (brown), E - Earth (green/yellow), N - Neutral (blue).
- Switch on and check for correct operation



WARNING

This product must be disconnected from the circuit if subjected to any high voltage or insulation resistance testing. Irreparable damage will occur if this instruction is not followed.

Care should be taken when installing into high 'clay' content soils which naturally retain water and have poor drainage. We recommend IP67 or IP68 products to be installed where these environmental conditions occur as IP65 luminaires will likely be compromised.

This product is not suitable for installation in or near a coastal or marine environment.

GENERAL

This product contains a light source of energy efficiency class C to Regulation (EU) No. 2019/2015 and (UK) 2021 No. 1095.

This product contains a non-replaceable LED light source and a non-replaceable control gear.





Clean with a soft dry cloth only, do not use aggressive cleaning products or solvents which may damage the product.

Do not use any source of high-pressure washers to maintain or clean this luminaire.

A light film of acid-free oil is recommended after installation and maintained periodically (2-3 times a year) to aid corrosion prevention.

This product is non-dimmable.

If the external supply cable of this luminaire is damaged, it should be replaced exclusively by the manufacturer or a similarly qualified person in order to avoid a hazard.

This product should be dismantled for disposal when it reaches the end of its life. Please see website for dismantling instructions.

This product should be recycled in the correct manner when it reaches the end of its life. Check local authorities for where facilities exist

WARRANTY

This product has a warranty of 1 year from date of purchase. Failure to install this product in accordance with the current edition of the IEE Wiring Regulations (BS7671), improper use, or removal of the batch code will invalidate the warranty. If this product should fail within its warranty period, it should be returned to the place of purchase for a free of charge replacement. ML Accessories does not accept responsibility for any installation costs associated with the replacement product. Your statutory rights are not affected. ML Accessories reserve the right to alter product specification without prior notice.

SUPPLIED BY:

(UK) MANUFACTURER ML ACCESSORIES LTD,
UNIT E CHILTERN PARK,

BOSCOMBE ROAD, DUNSTABLE LU5 4LT, WWW.MLACCESSORIES.CO.UK









52!

(EU) AUTHORISED REPRESENTATIVE SLV LIGHTING GROUP, DAIMLERSTRASSE 21-23.

52531 ÜBACH-PALENBERG, GERMANY EMAIL: EPREL@GROUP.SLV.COM

MADE IN CHINA